



## QUADRO 400

## QUADRO 800

## QUADRO 1200

	QUADRO 400	QUADRO 800	QUADRO 1200
<b>Dimensions</b>	280x400x92 mm	280x540x92 mm	280 x 640 x 92 mm
<b>Air output</b>	400 m <sup>3</sup> / h	800 m <sup>3</sup> /h	1200 m <sup>3</sup> / h
<b>Connection voltage</b>	210 - 250 Volt	210 - 250 Volt	210 - 250 Volt
<b>Connection dimension</b>	222 x 90 mm	222 x 90 mm	222 x 90 mm
<b>Article No.</b>	8740	8780	8712
<b>Weight</b>	3,0 kg	6,0 kg	6,5 kg
<b>Packaging dimension</b>	660 x 310 x 110 mm	660 x 310 x 110 mm	660 x 310 x 110 mm
<b>Packaging unit</b>	1 Pc.	1 Pc.	1 Pc.

Contact time / incident flow velocity: depending on degree of contamination 0.1-1 sec, 2 min / max. pressure difference: at 2 m/s incident flow, 100 Pa

Electrical operation: primary: 210-250 V, 50Hz | secondary: HS approx. 5 KV, 10 Watt Power consumption: max. 10 Watt, max. 3.65 KW p.a. | Standby consumption: max. 0.5 Watt

Technical modifications reserved!

