



PLANO 400

PLANO 500

PLANO 600

PLANO 800

	PLANO 400	PLANO 500	PLANO 600	PLANO 800
Dimensions	210 x 250 x 87 mm	250 x 250 x 87 mm	350 x 250 x 87 mm	450 x 250 x 110 mm
Air output	400 m ³ / h	500 m ³ / h	600 m ³ / h	800 m ³ / h
Connection voltage	210 - 250 Volt	210 - 250 Volt	210 - 250 Volt	210 - 250 Volt
Connection dimension & Article No.	ø 150 mm 8940 ø 120 mm 8948	ø 150 mm 8950 ø 120 mm 8958	ø 150 mm 8960 ø 120 mm 8968	ø 150 mm 8980 ø 120 mm 8988
Weight	2,2 kg	2,5 kg	3,1 kg	3,8 kg
Packaging dimension	260 x 220 x 320 mm	260 x 220 x 320 mm	260 x 220 x 390 mm	260 x 220 x 490 mm
Packaging unit	1 Pc.	1 Pc.	1 Pc.	1 Pc.

Standard shipping: Stainless steel. All PLANOs also available in black and white powder coated.

Contact time / face velocity: depending on degree of contamination 0.1-1 sec, 2 min / max. pressure difference: at 2 m/s face velocity, 100 Pa.

Electrical operation: primary: 210-250 V, 50Hz | secondary: HS approx. 5 KV, 10 Watt

Power consumption: max. 10 Watt, max. 3.65 KW p.a. | Standby consumption: max. 0.5 Watt

Subject to technical changes!

